

RACE

TRACK

NAME

CITY / COUNTRY

DATE

TEMPERATURE	AIR	TRACK	
QUALIFYING POSITION	BEST LAP TIME	FINAL POSITION	RACE LENGTH
SEC		MIN	
TRACK CONDITION <input type="checkbox"/> TECHNICAL <input checked="" type="checkbox"/> MIXED <input type="checkbox"/> FAST			
TRACTION <input type="checkbox"/> LOW <input checked="" type="checkbox"/> MEDIUM <input type="checkbox"/> HIGH			

GEAR RATIO CHART

Spur	Spur 1st	Spur 2nd
Pinion	60 61 62	56 57 58
1st	<input type="checkbox"/> 18T <input checked="" type="checkbox"/> 19T <input type="checkbox"/> 20T	<input type="checkbox"/> <input checked="" type="checkbox"/> <input type="checkbox"/>
2nd	<input type="checkbox"/> 23T <input checked="" type="checkbox"/> 24T <input type="checkbox"/> 25T	<input type="checkbox"/> <input checked="" type="checkbox"/> <input type="checkbox"/>

SHOCK

Oil: 500 CST 1 HOLE 2 HOLE

Shock Piston: 1 HOLE 2 HOLE

Hole Size: F mm, R mm

Spring: WHITE


TIRE

Front Left	32°	Tire Shore	Rear Left	35°
Front Right	32°		Rear Right	35°
Front Left	68 mm	Tire Ø	Rear Left	75 mm
Front Right	68 mm		Rear Right	75 mm
Tire Additive		<input type="text"/>		

BODY

Bumper: Standard Cut

Body Mount Distance: mm



Body: SPIDER WING 8 mm

ENGINE

Engine	Pipe
Plug	Carb Dia <input type="text"/> mm
Fuel	Head Shims <input type="text"/> mm

CLUTCH

Clutch Bell	Aluminum	Clutch Shoes	YELLOW
Spring Load	0.8 mm	Bell Clearance	0.6 mm

NOTE

R839008 BRACE

WHEEL BASE: 4 mm, 1 mm

BUMP STEER: 0 mm


CASTER: 2 mm

SHIM UNDER SHOCK: mm

R839009 BRACE

SHIM UNDER SHOCK: mm

REAR UPRIGHTSHIMS: 3 mm



FRONT ARM: S M H R832012

STEERING BLOCK SETUP

CENTER R806021	CENTER	BACKWARD	FORWARD	LOWER	UPPER
<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

ECCENTER HUB

<input checked="" type="checkbox"/> Up	<input type="checkbox"/> Middle	<input type="checkbox"/> R806021
--	---------------------------------	----------------------------------

REAR ARM: S M H

FRONT

RIDE HEIGHT: 8 mm

FRONT UPPER ARM:

WHEEL SHIMS: 1.0 mm

CAMBER: R 1.5°, L 1.5°

REAR

RIDE HEIGHT: 8.5 mm

2 HOLES INSIDE, 1 HOLE OUTSIDE

CAMBER: R 3.0°, L 3.0°

WHEEL SHIMS: 1.2 mm

DOWN STOP: 0 mm

FRONT LOW ARM:

REAR ROLL CENTER:

I-TYPE:

REAR UPPER LINK:

DOWN STOP: 8 mm

REAR TOE: IN 3°

FRONT TOE: OUT 1.5°

REAR ANTI-ROLL BAR: 2.8 mm

FRONT ANTI-ROLL BAR: 2.2 mm

UPPER DECK: FIX REMOVED

ACKERMAN: 10mm 9mm 8.5mm

UPPER DECK: FIX FLEX

CHASSIS WEIGHT ADJUSTMENT: REMOVED, R838008 CHASSIS COVER

TRACK WIDTH: 262 mm

TRACK WIDTH: 252 mm