

RACE: SIGP 2024
 TRACK: ARC
 NAME: Hai Feng Wang (Motor King)
 CITY / COUNTRY: China Ximen
 DATE: _____

TEMPERATURE: _____ AIR: _____ TRACK: _____

QUALIFYING POSITION: 1 BEST LAP TIME: 15.2 SEC FINAL POSITION: 1 RACE LENGTH: 4 MIN

TRACK CONDITION: TECHNICAL MIXED FAST
 TRACTION: LOW MEDIUM HIGH

GEAR RATIO CHART

Spur Pinion \ 56	56	57	58	60	61	62
22	6.11	6.22	6.33	6.55	6.65	6.76
23	5.84	5.95	6.05	6.26	6.37	6.47
24	5.60	5.70	5.80	6.00	6.10	6.20
25	5.38	5.47	5.57	5.76	5.86	5.95
26	5.17	5.26	5.35	5.54	5.63	5.72
27	4.98	5.07	5.16	5.33	5.42	5.51
28	4.80	4.89	4.97	5.14	5.23	5.31
29	4.63	4.72	4.80	4.97	5.05	5.13
30	4.48	4.56	4.64	4.80	4.88	4.96

SHOCK: Front (Oil: 750 CST, Spring: _____), Rear (Oil: 750 CST, Spring: _____)
 SHOCK PISTON: F: std mm, R: std mm
 HOLE SIZE: _____

TIRE: Front Left: 32°, Front Right: 32°, Rear Left: 35°, Rear Right: 35°
 Tire Shore: _____
 Tire Ø: Front Left: 70 mm, Front Right: 70 mm, Rear Left: 76 mm, Rear Right: 76 mm
 Tire Additive: _____

BODY: Bumper (Standard/Cut), BODY MOUNT DISTANCE: std mm

WING: 10 mm

NOTE

ACE 4S 6000mAh
 HW XR8 PRO G3
 HW 2800 KV

WHEEL BASE: 1 mm
 BUMP STEER: 0 mm
 CASTER: 2 mm
 TOWER POSITION: _____ mm
 FRONT ARM: S M H

STEERING BLOCK SETUP: CENTER R806021 (checked), CENTER, BACKWARD, FORWARD, LOWER, UPPER
 REAR ARM: S M H

REAR UPRIGHTSHIMS: 3 mm
 ECCENTER HUB: Up Middle R806021

FRONT: RIDE HEIGHT: 8 mm
 FRONT UPPER ARM:
 CAMBER: R 1.2°, L 1.2°
 WHEEL SHIMS: 1 mm

REAR: 1 HOLE, 2 HOLES INSIDE, 2 HOLES OUTSIDE
 RIDE HEIGHT: 9 mm
 CAMBER: R 3°, L 3°
 WHEEL SHIMS: 1.2 mm

DOWN STOP: 0 mm
 FRONT LOW ARM:
 REAR ROLL CENTER:
 I-TYPE: _____

REAR UPPER LINK:
 DOWN STOP: 9 mm

WHELL DISK: _____
 REAR TOE: IN 3°
 FRONT TOE: OUT 1°
 REAR ANTI-ROLL BAR: 2.8 mm
 UPPER DECK: FIX FLEX
 FRONT ANTI-ROLL BAR: 2.0 mm
 R838003: FIX REMOVED
 ACKERMAN: 10mm 9mm 8.5mm
 STIFFENER: REMOVED R828004
 TRACK WIDTH: 263.5 mm
 TRACK WIDTH: 231.5 mm