R8.0 2016 SET-UP SHEET

ARC

RACE	
TRACK	
NAME	
CITY / COUNTRY	
DATE	

TEMPERATURE	AIR	TRACK

QUALIFYING POSITION	BEST LAPTIME (SEC)	FINAL POSITION	RACE LENGTH (MIN)

TRACK CONDITION ☐ TECHNICAL ☐ MIXED ☐ FAST

TRACTION ☐ LOW ☐ MEDIUM ☐ HIGH

GEAR RATIO CHART

Spur	Spur 1st			Spur 2nd		
Pinion	60	61	62	56	57	58
1st 19T	☐	☐	☐	5.37	5.46	5.56
2nd 24T	7.26	7.38	7.51	☐	☐	☐

SHOCK

Front		Rear
OIL CST	☐ 1 HOLE ☐ 2 HOLE	☐ 1 HOLE ☐ 2 HOLE OIL CST
SPRING	SHOCK PISTON HOLE SIZE mm / mm	SPRING

TIRE

Front		Rear
Front Left ° / Front Right °	Tire Shore	Rear Left ° / Rear Right °
Front Left mm / Front Right mm	Tire Ø	Rear Left mm / Rear Right mm
	Tire Additive	

BODY

Bumper	
	Standard
	Cut

BODY MOUNT DISTANCE mm

BODY		WING	mm

ENGINE

Engine		Pipe	
Plug		Carb Dia	mm
Fuel		Head Shims	mm

CLUTCH

Clutch Bell		Clutch Shoes	
Spring Load	mm	Bell Clearance	mm

NOTE

FRONT BODY TOWER	
Front	Rear
☐	☐

DISK	
☐	Yes
☐	No

CASTER mm

WHEEL BASE mm

BUMP STEER mm

DISK	
☐	Yes
☐	No

REAR UPRIGHT SHIMS mm

ECCENTER HUB		
☐ Up	☐ Middle	☐ Low

FRONT

RIDE HEIGHT mm

DOWN STOP mm

WHEEL SHIMS mm

CAMBER °

FRONT UPPER ARM	
☐	Front Upper Arm Short
☐	Front Upper Arm Medium
☐	Front Upper Arm Long

REAR

RIDE HEIGHT mm

DOWN STOP mm

CAMBER °

WHEEL SHIMS mm

LONG	SHORT
☐ R802042	☐ R802041

+0mm	+2mm
☐ R801021	☐ R801022

REAR ROLL CENTER		
☐	☐	☐

REAR UPPER LINK		
☐	☐	☐

REAR TOE

IN	°

FRONT TOE

OUT	°
IN	°

REAR ANTI-ROLL BAR mm

FRONT ANTI-ROLL BAR mm

UPPER DECK	
☐	FIX
☐	FLEX

ACKERMAN		

TRACK WIDTH mm

TRACK WIDTH mm