

RACE

TRACK

NAME

CITY / COUNTRY

DATE

TEMPERATURE AIR TRACK

QUALIFYING POSITION BEST LAP TIME SEC FINAL POSITION RACE LENGTH MIN

TRACK CONDITION TECHNICAL MIXED FAST

TRACTION LOW MEDIUM HIGH

GEAR RATIO CHART

Spur Pinion \ 56	57	58	60	61	62	
22	6.11	6.22	6.33	6.55	6.65	6.76
23	5.84	5.95	6.05	6.26	6.37	6.47
24	5.60	5.70	5.80	6.00	6.10	6.20
25	5.38	5.47	5.57	5.76	5.86	5.95
26	5.17	5.26	5.35	5.54	5.63	5.72
27	4.98	5.07	5.16	5.33	5.42	5.51
28	4.80	4.89	4.97	5.14	5.23	5.31
29	4.63	4.72	4.80	4.97	5.05	5.13
30	4.48	4.56	4.64	4.80	4.88	4.96

SHOCK

Front: OIL 500 CST 1 HOLE 2 HOLE SPRING White

Rear: OIL 500 CST 1 HOLE 2 HOLE SPRING White

SHOCK PISTON: 1 HOLE 2 HOLE

HOLE SIZE: F mm R mm

TIRE

Front Left: 32° Front Right: 32°

Rear Left: 35° Rear Right: 35°

Tire Shore:

Tire Ø: Front Left: 68mm Front Right: 68mm Rear Left: 75mm Rear Right: 75mm

Tire Additive:

BODY

Bumper: Standard Cut

BODY MOUNT DISTANCE: 21 mm

Spider WING 2 mm

NOTE

R839008 BRACE

R838104 Yes No

BUMP STEER: 0 mm

CASTER: 2 mm

SHIM UNDER SHOCK: mm

WHEEL BASE: 4 mm 1 mm

TOWER POSITION: +4 mm

R839009 BRACE

SHIM UNDER SHOCK: mm

REAR UPRIGHTSHIMS: 3 mm

STEERING BLOCK SETUP

Center R806021:

Center:

Backward:

Forward:

Lower:

Upper:

DISK: Yes No

ECCENTER HUB

UP CENTER R806021

FRONT

RIDE HEIGHT: 8 mm

FRONT UPPER ARM:

WHEEL SHIMS: 1.0 mm

CAMBER: R 1.5° L 1.5°

REAR

1 HOLE 2 HOLES INSIDE 2 HOLES OUTSIDE

RIDE HEIGHT: 8.5 mm

CAMBER: R 3.0° L 3.0°

WHEEL SHIMS: 1.2 mm

DOWN STOP: 0 mm

FRONT LOW ARM:

REAR ROLL CENTER:

I-TYPE:

REAR UPPER LINK:

DOWN STOP: 8 mm

REAR TOE: IN 3°

FRONT TOE: OUT 1.5° IN 0°

FRONT ANTI-ROLL BAR: 2.2 mm

REAR ANTI-ROLL BAR: 2.8 mm

ACKERMAN: 10mm 9mm 8.5mm

TRACK WIDTH: 262 mm

TRACK WIDTH: 252 mm