RBS

SET-UP SHEET — ARC

ver 2018.08

RACE

TRACK

NAME

CITY / COUNTRY

DATE

TEMPERATURE	AIR	TRACK

QUALIFYING POSITION	BEST LAPTIME	FINAL POSITION	RACE LENGTH
	SEC		MIN

TRACK CONDITION ☐ TECHNICAL ☐ MIXED ☐ FAST

TRACTION ☐ LOW ☐ MEDIUM ☐ HIGH

GEAR RATIO CHART

MOTOR SPEC

Pinion \ Spur	60	61	62
16T	☐ 3.75	☐ 3.81	☐ 3.88
17T	☐ 3.53	☐ 3.59	☐ 3.65
18T	☐ 3.33	☐ 3.39	☐ 3.44

TIRE

TIRE BRAND

Front | Rear

Front Left °	**Tire Shore**	Rear Left °
Front Right °		Rear Right °
Front Left mm	**Tire Ø**	Rear Left mm
Front Right mm		Rear Right mm
☐ ☐	**Tire Additive**	☐ ☐

NOTE

FRONT

CAMBER °

SHIM mm

TRACK WIDTH mm

RIDE HEIGHT mm

FRONT ECCENTRIC HUB

REAR — FRONT

REAR

REAR DEFLECTOR ☐ Yes ☐ No

REAR MAIN SHAFT ☐ Wide ☐ Narrow

TRACK WIDTH mm

RIDE HEIGHT mm

REAR ECCENTRIC HUB

Center

BATTERY LAY OUT

☐ 2S Standard Lipo Side by Side
☐ 2S Short Lipo Side by Side
☐ 4S Single Lipo Pack
☐ 2S Standard Lipo Stand Up
☐ 2S Short Lipo Standard Up

ACKERMAN PLATE

☐ ☐ ☐

BODY MOUNT PLATE

☐ Yes ☐ No

BUMPER

Standard
Cut

BODY MOUNT DISTANCE mm

CENTER O'RING

mm

FRONT SWING O'RING

☐ Soft (R104030)
☐ Standard (R104002)
☐ Hard (R104008)

CASTER ANGLE

☐ 4°
☐ 8°
☐ 12°

BODY | **WING** mm